

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : APRON XL 350 ES
Design code : A9642C
Product Registration Number : Pfl.Reg.Nr. 3779

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Fungicide, Seed treatment

1.3 Details of the supplier of the safety data sheet

Company : Syngenta Agro GmbH
Anton-Baumgartner-Strasse 125/2/3/1
A-1230 Wien
Austria

Telephone : +43 (0)1 6623130 600
Telefax : +43 1 6623130250
E-mail address of person responsible for the SDS : franz.michlits@syngenta.com

1.4 Emergency telephone number

Emergency telephone number : 0800 43 577 96 (HELPSYN)
Vergiftungsinformationszentrale in Wien, Tel.-Nr.: 01-4064343

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H302: Harmful if swallowed.
Eye irritation, Category 2 H319: Causes serious eye irritation.

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H302 Harmful if swallowed.
H319 Causes serious eye irritation.

Supplemental Hazard Statements : For professional users only.

EUH401 To avoid risks to human health and the environment, comply with the instructions for use.

EUH208 Contains 1,2-benzisothiazol-3-one.
May produce an allergic reaction.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284 Wear respiratory protection.

Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

metalaxyl-M (ISO)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
metalaxyl-M (ISO)	70630-17-0 612-163-00-0	Acute Tox. 4; H302 Eye Dam. 1; H318	>= 30 - < 50
poly(oxy-1,2-ethanediyl), -[2,4,6-tris(1-phenylethyl)phenyl]- -hydroxy-	99734-09-5	Aquatic Chronic 3; H412	>= 2,5 - < 10
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 0,0025 - < 0,025

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Have the product container, label or Safety Data Sheet with you when calling the emergency number, a poison control center or physician, or going for treatment.
- If inhaled : Move the victim to fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Keep patient warm and at rest.
Call a physician or poison control centre immediately.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with plenty of water.
If skin irritation persists, call a physician.
Wash contaminated clothing before re-use.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Remove contact lenses.
Immediate medical attention is required.
- If swallowed : If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Nonspecific
No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : There is no specific antidote available.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Extinguishing media - small fires
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Extinguishing media - large fires
Alcohol-resistant foam
or
Water spray

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear full protective clothing and self-contained breathing apparatus.

Further information : Do not allow run-off from fire fighting to enter drains or water courses.
Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Clean with detergents. Avoid solvents.
Retain and dispose of contaminated wash water.

6.4 Reference to other sections

For disposal considerations see section 13., Refer to protective measures listed in sections 7 and 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : No special protective measures against fire required.
Avoid contact with skin and eyes.
When using do not eat, drink or smoke.
For personal protection see section 8.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : No special storage conditions required. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs.

Storage class (TRGS 510) : 12, Non Combustible Liquids

Recommended storage temperature : 0 - 35 °C

7.3 Specific end use(s)

Specific use(s) : For proper and safe use of this product, please refer to the approval conditions laid down on the product label.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
metalaxyl-M (ISO)	70630-17-0	TWA	5 mg/m ³	Syngenta

8.2 Exposure controls

Engineering measures

THE FOLLOWING RECOMMENDATIONS FOR EXPOSURE CONTROLS/PERSONAL PROTECTION ARE INTENDED FOR THE MANUFACTURE, FORMULATION AND

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

PACKAGING OF THE PRODUCT. FOR COMMERCIAL APPLICATIONS AND/OR ON-FARM APPLICATIONS CONSULT THE PRODUCT LABEL.

Containment and/or segregation is the most reliable technical protection measure if exposure cannot be eliminated.

The extent of these protection measures depends on the actual risks in use.

Maintain air concentrations below occupational exposure standards.
Where necessary, seek additional occupational hygiene advice.

Personal protective equipment

Eye protection : Tightly fitting safety goggles
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Equipment should conform to EN 166

Hand protection

Remarks : No special protective equipment required.

Skin and body protection : No special protective equipment required.
Select skin and body protection based on the physical job requirements.

Respiratory protection : No personal respiratory protective equipment normally required.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Protective measures : The use of technical measures should always have priority over the use of personal protective equipment.
When selecting personal protective equipment, seek appropriate professional advice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : clear

Colour : yellow

Odour : weak

Odour Threshold : No data available

pH : 3 - 7
Concentration: 1 % w/v

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

Melting point/range	:	No data available
Boiling point/boiling range	:	> 90 °C (1.013,25 hPa)
Flash point	:	Method: Seta closed cup does not flash
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	1,07 g/cm ³ (20 °C)
Solubility(ies)		
Solubility in other solvents	:	Miscible
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	435 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	44,2 mPa.s (20 °C) 16,2 mPa.s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Surface tension : 27,1 mN/m, 100 %, 20 °C

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure :
Ingestion
Inhalation
Skin contact
Eye contact

Acute toxicity

Product:

Acute oral toxicity : LD50 (Rat, female): > 1.000 - < 3.000 mg/kg

Acute dermal toxicity : LD50 (Rat, male and female): > 4.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Components:

metalaxyl-M (ISO):

Acute oral toxicity : LD50 (Rat, male): 953 mg/kg

LD50 (Rat, female): 375 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 2,29 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Highest attainable concentration

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

toxicity

poly(oxy-1,2-ethanediyl), -[2,4,6-tris(1-phenylethyl)phenyl]- -hydroxy-:

Acute oral toxicity : LD50 Oral (Rat): 5.000 mg/kg

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 1.020 mg/kg

Skin corrosion/irritation

Product:

Species : Rabbit
Result : No skin irritation

Components:

metalaxyl-M (ISO):

Species : Rabbit
Result : No skin irritation

1,2-benzisothiazol-3(2H)-one:

Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Components:

metalaxyl-M (ISO):

Species : Rabbit
Result : Risk of serious damage to eyes.

1,2-benzisothiazol-3(2H)-one:

Result : Risk of serious damage to eyes.

Respiratory or skin sensitisation

Product:

Test Type : Buehler Test
Species : Guinea pig
Result : Did not cause sensitisation on laboratory animals.

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

Components:

metalaxyl-M (ISO):

Species : Guinea pig
Result : Did not cause sensitisation on laboratory animals.

1,2-benzisothiazol-3(2H)-one:

Result : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Components:

metalaxyl-M (ISO):

Germ cell mutagenicity-
Assessment : Animal testing did not show any mutagenic effects.

poly(oxy-1,2-ethanediyl), -[2,4,6-tris(1-phenylethyl)phenyl]- -hydroxy-:

Germ cell mutagenicity-
Assessment : In vitro tests did not show mutagenic effects

Carcinogenicity

Components:

metalaxyl-M (ISO):

Carcinogenicity -
Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Components:

metalaxyl-M (ISO):

Reproductive toxicity -
Assessment : No toxicity to reproduction

STOT - repeated exposure

Components:

metalaxyl-M (ISO):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

SECTION 12: Ecological information

12.1 Toxicity

Product:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 54,4 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
- NOEC (Desmodesmus subspicatus (green algae)): 32 mg/l
Exposure time: 72 h

Components:

metalaxyl-M (ISO):

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 271 mg/l
Exposure time: 96 h
- NOEC (Pseudokirchneriella subcapitata (green algae)): 19,7 mg/l
End point: Growth rate
Exposure time: 96 h
- Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
- Toxicity to fish (Chronic toxicity) : NOEC: 50 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 25 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

poly(oxy-1,2-ethanediyl), -[2,4,6-tris(1-phenylethyl)phenyl]- -hydroxy-:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 21 mg/l
Exposure time: 96 h

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

1,2-benzisothiazol-3(2H)-one:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

12.2 Persistence and degradability

Components:

metalaxyl-M (ISO):

Biodegradability : Result: Not readily biodegradable.

Stability in water : Degradation half life: 22,4 - 47,5 d
Remarks: Product is not persistent.

12.3 Bioaccumulative potential

Components:

metalaxyl-M (ISO):

Bioaccumulation : Remarks: Low bioaccumulation potential.

Partition coefficient: n-octanol/water : log Pow: 1,71 (25 °C)

12.4 Mobility in soil

Components:

metalaxyl-M (ISO):

Distribution among environmental compartments : Remarks: Metalaxyl has a range from low to very high mobility in soil depending on soil type.

Stability in soil : Dissipation time: < 50 d
Percentage dissipation: 50 % (DT50)
Remarks: Product is not persistent.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

Components:

metalaxyl-M (ISO):

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

poly(oxy-1,2-ethanediyl), -[2,4,6-tris(1-phenylethyl)phenyl]- -hydroxy-:

Assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).. This substance is not considered to be very persistent and very bioaccumulating (vPvB)..

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not dispose of waste into sewer.
Where possible recycling is preferred to disposal or incineration.
If recycling is not practicable, dispose of in compliance with local regulations.

Hazardous waste according to ÖNORM S 2100, key code 53103

Contaminated packaging : Empty remaining contents.
Triple rinse containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

Waste Code : 15 01 10, packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Other regulations:

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance when it is used in the specified applications.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



APRON XL 350 ES

Version 1.0 Revision Date: 25.02.2020 SDS Number: S1281633 This version replaces all previous versions.

H400 : Very toxic to aquatic life.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4 H302
Eye Irrit. 2 H319

Classification procedure:

Based on product data or assessment
Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

APRON XL 350 ES

Version	Revision Date:	SDS Number:	This version replaces all previous versions.
1.0	25.02.2020	S1281633	

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AT / EN